

# Panchromatic

## Yashica FR11 35 mm SLR Film Camera

### With OSAWA MC 1:3.8 75-150 mm Lens

This camera was designed with maximum ease of operation in mind and features fully automatic exposure control. Silicon photo-diode metering has been employed for instantaneous exposure readout and an exposure compensation dial is provided for adjustment in special lighting situations.

It is part of a whole system of Contax and Yashica accessory equipment to make possible an endless variety of uses. To begin with, it features the Contax/Yashica mount for accepting a wide range of Yashica and Zeiss T\* interchangeable lenses. Its feather-touch electromagnetic shutter release, in addition to making possible blur-free pictures, also enables use with a variety of remote control release systems such as cable switches and the wireless Infrared Controller Set. In addition, its electromagnetic release system permits use with the highly advanced RTF 540 electronic flash unit. And when both the RTF 540 and the Yashica Winder are used jointly with the FR 11, it is capable of sequential flash up to 2 frames per second.

- Type: TTL metering fully automatic exposure 35 mm SLR camera
- Lens Mount: Contax/Yashica mount.
- Negative Size: 24 x 36 mm
- Shutter: Electronically Controlled horizontal run focal plane shutter. Shutter speeds automatically varied between 4 sec. to 1/1000 sec. at AUTO setting, Bulb setting (B) for long exposure and electronic flash synchronization setting (I) for manual operation.
- Self Timer: Built-in lever type; releases in 7 sec.
- Shutter Release: Feather-touch electromagnetic release socket on camera body for auxiliary shutter release.
- Exposure Meter: TTL aperture-preferred fully automatic exposure control. Centre-weighted full aperture light metering via SPD cell.
- Exposure Check Button: Push Button/slide type; lockable with film advance lever slightly cocked.
- Exposure Range: Between EV 1 - 18 with f/1.4 standard lens using ASA film.

- Exposure Compensation: +2 EV
- ASA Film Speed Settings: ASA 12 – 3200
- Power Source: 6 V silver oxide battery (Eveready 544 Ucar 544, Mallory PX-28 or equivalent).
- Viewfinder: Through-the-lens reflex viewfinder; shows a field of approx. 92% of the actual picture area with an image magnification of 0.87X. Shutter speeds indicated by pointer from 1/1000 sec. - 1 sec.
- Focusing Screen: diagonal split-image centre spot with microprism collar.
- Film Advance: single-frame advance via film advance lever with 140 degree full stroke, or multiple short ratchet stroke advance; frame count registers on exposure counter. Sequential film advance to 2 fps with optional Yashica Winder unit.
- Film Rewind: via film rewind crank.
- Back Cover: Standard back opens by lifting out on film rewind crank.
- Other Features: Battery confirmation lamp; lens release button, memo holder, direct X contact accessory shoe.
- Size and Weight: 142.5 x 87 x 50 mm 650 grams (body only)

### Fitted Lens

The Osawa MC 75-150 mm f/ 3.8 is a telephoto zoom lens with constant lens speed for SLR 35mm cameras. The lens is multi-coated.

Format: 35mm SLR

Type: Zoom lens

Focusing: Manual Focus (MF)

Lens mounts: Yashica / Contax (35mm)

### Specifications:

- Focal length : 75-150 mm
- Max. Aperture : f/3.8
- Min. aperture : f/22
- Blades : 6
- Min. Focus (m.) : 1.9
- Filter Ø (mm.) : 49
- Weight : 500 g
- Length : 125 - 180 mm

## Note

Delivery to Mainland UK is at  
Standard Insured Courier Delivery Price up to 32 Kilos for Multiple Items

# Panchromatic